

2201C Coagulation Analyzer



Features

- 1- 1 channel (LED detector)
- 2- Easy keypad operation with LCD display
- 3- Internal thermal-sensitive printer; Electronically-linked pipette optional
- 4- Reagent position with magnetic rotor
- 5- Scattered light and percentage analysis ensure good results
- 6- Open reagent system with low consumption, close reagent on request
- 7- Large memory to store up to 6000 test results
- 8- QC and calibration program incorporated
- 9- Auto self-check when power on
- 10- Multi-language software available on request

System Specifications

Analysis Parameters	PT, APTT, TT, FIB, F2, F5, F7, F8, F9, F10, F11, F12, Heparin, APC-R, Protein S, Protein C
Principle	Scattered light with percentage analysis
Sample Volume Required	PT: 25ul
	APTT: 25ul
	TT: 25ul
	FIB: 25ul
Testing Channel	1 Channels
Light Source	Durable LED detector
Sample Position	5 positions
Reagent Position	2 positions (1 magnetic rotor included)
Testing Time	Normally 20-60 secs, Maximum time up to 600 secs
Minimum Reagent Consumption	30µL for APTT; 50µL for TT, FIB, PT
Position Warming-up	37°C(±0.5°C)
Memory	6,000 test results
Display	LCD display
Interface	RS-232
Input	Easy operation keypad
Output	Internal printer
Power supply	AC 110-220V±10%, 50-60Hz
Net Weight	5KG
Dimension LxWxH(mm)	270x270x120

Hiperion



Medizintechnik GmbH & Co.KG
 Carl-Zeiss-Str.18 D-6332 Roedermark, Germany